

# JET 530

## Technical sheet

### USES

|                 |                                     |
|-----------------|-------------------------------------|
| Recommended use | Banners, P.O.S, Signage, Stand      |
| Printing        | Printable side : outside            |
| Ink             | Solvent, Eco-solvent, UV, Latex Ink |

| CHARACTERISTICS | VALUES |      | UNITS | STANDARDS |
|-----------------|--------|------|-------|-----------|
|                 | WARP   | WEFT |       |           |

### GENERAL CHARACTERISTICS

|              |                             |                  |           |
|--------------|-----------------------------|------------------|-----------|
| Thickness    | 0.47                        | mm               | ISO 5084  |
| Base cloth   | 1100 dTex PES HT<br>990 den |                  |           |
| Coating      | PVC Lowick coating one side |                  |           |
| Finish       | Inkjet lacquer one side     |                  |           |
| Weight       | 560                         | g/m <sup>2</sup> | ISO 3801  |
| Translucency | 6                           | %                | XPT 54199 |
| Width        | 106 137 162 250 320         | cm               |           |
| Roll length  | 30 30 30 60 60              | ml               |           |

### FABRIC RESISTANCE

|                  |     |     |         |                |
|------------------|-----|-----|---------|----------------|
| Tensile strength | 210 | 200 | daN/5cm | NF EN ISO 1421 |
| Tear strength    | 25  | 20  | daN     | DIN 53.363     |
| Adhesion         | 7   |     | daN/5cm | NF EN ISO 2411 |
| Cold resistance  | -30 |     | °C      | NF EN 1876-2   |
| Warm resistance  | 70  |     | °C      | (24h)          |
| Fire resistance  | M2  |     |         | NF P 92 503    |
|                  | B1  |     |         | DIN 4102       |

Values may vary in a tolerance of +/-10%.  
Specification maybe modified and are subject to manufacturer's requisites.  
Product compatibility to the application is reserved to the users' appraisal.  
The buyer of our products is responsible for checking the validity of the above data.

SYSTEM  
LOWICK



RESOURCE

REACH  
COMPLIANCE

MADE IN  
FRANCE



**DICKSON COATINGS**  
415, avenue de Savoie  
F-38110 Saint-Clair-de-la-Tour  
Tel. (+33) 04 74 83 51 00  
Fax (+33) 04 74 83 51 01  
[www.dickson-coatings.com](http://www.dickson-coatings.com)



GLEN RAVEN™

Glen Raven™ is a trademark  
and Dickson® is a registered  
trademark of Glen Raven, Inc.