

# JET 550

## Technical sheet

### USES

Recommended use	Banners, Signage, Pole banners
Printing	Printable side : outside
Ink	Solvent, Eco-solvent, UV, Latex Ink

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

### GENERAL CHARACTERISTICS

Thickness	0.47	mm	ISO 5084
Base cloth	1100 dTex PES HT 990 den		
Coating	PVC Lowick coating one side		
Finish	Inkjet lacquer one side		
Weight	560	g/m <sup>2</sup>	ISO 3801
Translucency	6	%	XPT 54199
Width	76    106    137    162    250    250 278    320    320	cm	
Roll length	30    30    30    30    30    60 60    30    60	ml	

### FABRIC RESISTANCE

Tensile strength	210	200	daN/5cm	NF EN ISO 1421
Tear strength	25	20	daN	DIN 53.363
Adhesion	7		daN/5cm	NF EN ISO 2411
Cold resistance	-30		°C	NF EN 1876-2
Warm resistance	70		°C	(24h)
Fire resistance	< 100		mm/min	DIN 75 200
	NFPA 701			NFPA 701

Values may vary in a tolerance of +/-10%.

Specification maybe modified and are subject to manufacturer's requisites.

Product compatibility to the application is reserved to the users' appraisal.

The buyer of our products is responsible for checking the validity of the above data.



**DICKSON COATINGS**  
415, avenue de Savoie  
F-38110 Saint-Clair-de-la-Tour  
Tel. (+33) 04 74 83 51 00  
Fax (+33) 04 74 83 51 01  
[www.dickson-coatings.com](http://www.dickson-coatings.com)



**GLEN RAVEN™**

Glen Raven™ is a trademark and Dickson® is a registered trademark of Glen Raven, Inc.

Certified for  
**HP Latex Inks**

**SYSTEM  
LOWICK**



**RESOURCE**  
 **REACH**  
COMPLIANCE

**MADE IN  
FRANCE**